

MULTI-AXIS MILL/TURN CNC LATHES

CMZ TA25YS-640 Twin
Spindle (C & Y axis)

Capacity: Barfeed 65mm dia. -
Chucking: 250 mm dia.



Mazak SQT 250MY (C &
Y axis)

Capacity: Barfeed 63mm dia. -
Chucking: 250 mm dia.



Mazak SQT 18MY (C & Y
axis)

Capacity: Barfeed 63mm dia. -
Chucking: 250 mm dia.



Mazak SQT 15MA (C
axis)

Capacity: Barfeed 51mm dia. -
Chucking: 200 mm dia.



Mazak SQT 15MB (C
axis)

Capacity: Barfeed 51mm dia. -
Chucking: 200 mm dia.

CNC VERTICAL MACHINING CENTRES

BROTHER TC-32BN QT - High
Speed Twin Pallet.

5-Axis Nikken Rotary Head on
Pallet 1
4-Axis Nikken Trunnion on Pallet 2

Capacity: X = 550, Y =
400mm, Z = 415mm



Doosan Mynx 5400 Heavy Duty
with 4th Axis Head

Capacity: X = 1020, Y =
540mm, Z = 530mm



Hurco VMX50T VMC

Capacity: X = 1270, Y =
660mm, Z = 610mm



HAAS VFOE VMC with 4th Axis
Head

Capacity: X = 762, Y =
406mm, Z = 508mm



Hardinge VMC 1000 II with 5-
Axis Nikken Head

Capacity: X = 1020, Y =
510mm, Z = 510mm



EDM/WIRE-CUT MACHINES

Mitsubishi FX10K

Workpiece dimensions: 800 x 575 x
215mm
Machining range: 350 x 250 x
220mm



Mitsubishi SA10F

Workpiece dimensions: 800 x 575 x
215mm
Machining range: 350 x 250 x
220mm



LASER MARKING

Tykma ElectroX Mini
Lase XL with Rotary
Head

Capacity: Laser Marking Area
100 x 100mm



INSPECTION EQUIPMENT

- DEA – Mistral CMM
- Capacity: 700 x 700 x 500mm
- Aberlink 3D Solid Modelling Software
- Trimos Vertical 3
- Capacity: 900mm max height
- Federal Air Gauging
- Capacity: Probes are purchased as required
- Mitutoyo PJ 300 Profile Projector
- Range of Mitutoyo Digital Micrometers
- Range of Bowers Metrology XT Bore Micrometers

CONVENTIONAL MACHINES

- Centre Lathes (up to 2 Metres between Centres)
- Universal Turret Mills
- Surface Grinders

CAD/CAM

OneCNC-XR6 Mill Professional, XR7 Turn Professional

File format includes: IGES, STP, DWG, DWF, DGN, DXF, PDF, TIF.